



Opteon™ SF30

Specialty Fluid

Next Generation Low GWP Precision Cleaning Fluid

Technical Information

Introduction

Opteon™ SF30 is a proprietary azeotrope of hydrofluoroolefin (HFO) specialty fluid and trans-1,2-dichloroethylene. It is designed for use in ultra-low residue precision cleaning for highly demanding markets, such as aerospace, automotive, precision electronics, and optics, where failure is not an option.

Opteon™ SF30 is a safe, nonflammable, and environmentally friendly solvent with low global warming potential (GWP) (<2.5) and does not contain any fluorinated greenhouse gases (as listed in Annex 1 of the EU regulations 517/2014). Opteon™ SF30 can replace high GWP hydrofluorocarbon (HFC)- and hydrofluoroether (HFE)-based precision cleaning solvents, as well as HCFC-225, HCFC-141b, CFC-113, methyl chloroform (1,1,1-TCA), methylene chloride, perfluorocarbons (PFCs), chlorofluorocarbons (CFCs), and aqueous cleaners in many industrial applications.

Features and Benefits

- Superior cleaning performance with enhanced solvency power
- Fast drying with an optimum boiling point (29.1 °C [84.4 °F]), allows cleaned parts to be processed and used immediately
- High soil loading capacity boosts productivity by reducing equipment downtime associated with solvent change-outs
- Product maintains compositional stability during use (azeotrope)
- Maintenance free: No stabilizer maintenance required

- No surfactants needed: Removes extra washing steps to achieve residue-free cleaning
- Recyclable and reusable: Reduces cost of ownership and environmental footprint
- Nonflammable
- Low odor and toxicity
- Excellent environmental profile: Low GWP (<10), EU 517/2014 compliant

Typical Applications

- Precision cleaning
- Vapor degreasing
- Ultrasound cleaning
- Cold cleaning
- Oil, grease, and silicone removal
- Aerosol solvent*
- Particle removal
- Heat transfer fluid for chillers, heat pipes, and vapor chambers

*Not available for use in European Union; certain restrictions apply. Contact Chemours or your local technical representative for additional information.



Chemours™

Table 1. Physical Properties

Property	Units	Opteon™ SF30	SOLKANE 365mfc
Boiling Point	°C	29.1	40.2
	°F	84.4	104.4
Liquid Density ⁽¹⁾	g/cm ³	1.33	1.27
	lb/gal	11.1	10.6
Saturated Vapor Density ⁽¹⁾	kg/m ³	5.09	6.98 ⁽²⁾
	lb/ft ³	0.32	0.44 ⁽²⁾
Surface Tension ⁽¹⁾	dyn/cm	16.4	N.D.
Vapor Pressure ⁽¹⁾	kPa	86.3	53 ⁽²⁾
	psia	12.5	7.7 ⁽²⁾
Viscosity ⁽¹⁾	cP	0.33	0.45 ⁽²⁾
Freezing Point	°C	<-80	-35
	°F	<-112	-31
Molecular Weight	g/mole	139.6	148.1
Kb Value		20	13
Heat Capacity ⁽¹⁾	kJ/kg·°C	1.19	N.D.
Liquid Thermal Conductivity ⁽¹⁾	mW/m·K	84.2	10.3
Vapor Flammability in Air			
Lower Limit	vol%	None	3.6
Upper Limit	vol%	None	13.3

⁽¹⁾Values reported are at 25 °C (77 °F). ⁽²⁾Values reported at 20 °C (68 °F), unless otherwise specified. N.D. refers to no reference data available. All data compiled was furnished from publicly available sources.

Table 2. Density and Vapor Pressure Change with Temperature

Temperature (°C)	Vapor Pressure (kPa)	Density (g/cm ³)
0	30.30	1.38
10	47.44	1.36
20	71.57	1.33
30	104.56	1.31
40	148.47	1.28
50	205.59	1.26
60	278.42	1.23

Cleaning Process

Opteon™ SF30 has broad range cleaning capabilities. It is ideally suited for use in precision cleaning, vapor degreasing, and ultrasonic cleaning. **Table 3** lists some typical soils that can be cleaned with Opteon™ SF30.

Contact Chemours to initiate a cleaning trial in one of our regional cleaning laboratories or obtain a sample for on-site testing.

Table 3. Soils Cleaned with Opteon™ SF30

Cutting Oils	Hydraulic Oils
Mineral Oils	Waxes
Gear Oils	Vacuum Oils
Heavy Greases	Stamping Oils
Fluorinated Oils	Refrigerant Oils
Silicone Oils	Silicone Greases

Materials Compatibility

Opteon™ SF30 is characterized by good compatibility with a wide selection of metals, for example, stainless steel, copper, brass, and aluminum. Opteon™ SF30 is compatible with most plastics and elastomers, as shown in **Table 4**. Individual plastic and elastomeric formulations can vary with the manufacturer; therefore, the best assurance of material compatibility can be recommended after testing under conditions expected during normal operation. Contact your local technical representative for specific material compatibility concerns.

Table 4. Plastics/Elastomers Compatibility*

Plastics		Elastomers	
Compatible	Incompatible	Compatible	Incompatible
Polyethylene	Polystyrene	Teflon™	Silicone
Polypropylene	Polycarbonate	Kalrez	Hypalon
Teflon™	ABS	Ryton	EPDM Rubber
Polyester	Polyacrylate	PTFE w/EPDM	Viton™
Nylon	Acrylic (PMMA)	PTFE w/Neoprene	Buna N
FEP/PFA	Polysulfone	Parafluor	Fluorosilicone
Halar			
Kynar			

*Material composition varies depending upon compounding agents, plasticizers, processing, etc. Specific materials should be tested for compatibility with solvent prior to use.

Safety, Toxicity, and Environmental

Opteon™ SF30 exhibits no closed, open cup flash point or vapor flammability limits. Opteon™ SF30 is classified as a nonflammable liquid by NFPA and DOT. Safety, toxicity, and environmental data are shown in **Table 5**.

Table 5. Safety, Toxicity, and Environmental Properties

Property	Units	Opteon™ SF30
Flash Point, OC, ASTM D1310	°C (°F)	None
Flash Point, CC, ASTM D56	°C (°F)	None
Vapor Flammability in Air		
Lower Limit	vol%	None
Upper Limit	vol%	None
Ozone Depletion Potential	-	Negligible
Global Warming Potential	-	<2.5
Volatile Organic Compounds (VOCs)	g/L	335
Occupational Exposure Limit, 8-hr TWA	ppm	425

Storage and Handling

Opteon™ SF30 is thermally stable and does not fractionate, oxidize, or degrade during storage. It is recommended to store containers in a clean and dry area, and protect them from freezing and excessive temperatures of 46 °C (115 °F). When stored properly, an unopened package has an indefinite shelf life. Package sizes for Opteon™ SF30 are 208 L (55 gal) drums and 19 L (5 gal) pails.

For additional information on Opteon™ SF30 or other specialty fluids products by Chemours, please visit vertrel.com or call 800-969-4758.

The information set forth herein is furnished free of charge and based on technical data that Chemours believes to be reliable. It is intended for use by persons having technical skill, at their own risk. Because conditions of use are outside our control, Chemours makes no warranties, expressed or implied, and assumes no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe, any patents or patent applications.

© 2019 The Chemours Company FC, LLC. Opteon™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC. Chemours™ and the Chemours Logo are trademarks of The Chemours Company.